kiosk

SUNMI K2













SUNMI K2







os os

Android 7.1 SUNMI OS



CPU



Memory

Support MicroSD(TF) up to 128GB



Display

G + G capacitive screen supports 10 touch points



Camera (Optional)

3D structured light camera Support FR payment membership verification, etc.



Scanner

on mobile screen



Printer

with automatic cutter Support 80mm OD paper roll Print speed up to 150mm/s (max)



Speaker

2*3W(stereo)



Wi-Fi

IEEE 802.11 a/b/g/n 2.4/5 GHz



Ethernet

self-adaptive



Port

1× Micro-USB Debug Port



Size(WDH)

Floor-standing: 540*490*1850mm



Weight

Wall-mounted: 16.5Kg Floor-standing: 45Kg



Power input

AC200~240V



Environment

Working temperature: 0 ~ 40°C Storage temperature: -20°C ~ 55°C

- Actual memory will be reduced due to a number of factors and may vary. Operating system also occupies some memory.

 The actual specs of products launched to the market shall take precedence over the info listed in this catalogue; any change may be made without prior notification.

kiosk

SUNMI K2

Retail Version

- Extremely reliable facial recognition (FR) camera with 3D structured light tech.
- 24" full HD touch screen supports 10-point touch.
- International famous scanner scans commodity barcode & payment QR code.
- Japanese Seiko printer supports till roll of 80/58mm, with automatic cutter.

App Store management, kiosk mode, canary deployment... powered by SUNMI OS.









Barcode

Verification

Payment

QR code





Payment







CPU

Six-core 1.8GHz



Memory

16G ROM+ 4G RAM Support MicroSD(TF) up to 128GB



Display

G + G capacitive screen supports 10 touch points



Camera (Optional)

3D structured light camera Support FR payment membership verification, etc.



Barcode Reader

mobile screen and printed barcodes



Printer

Support 80mm OD paper roll Print speed up to 150mm/s (max)



Wi-Fi

IEEE 802.11 a/b/g/n 2.4/5 GHz



Ethernet

10/100/1000M Ethernet self-adaptive



Port

1× Micro-USB Debug Port 5× USB TypeA port



Size(WDH)

394*171*1017mm Floor–standing: 1018*645*1850mm



Weight

Wall-mounted: 16.5Kg Floor-standing with table: 58Kg



Power input

AC100~120V AC200~240V



Environment

Working temperature: 0 ~ 40°C Storage temperature: -20°C ~ 55°C

- Note:

 1. Actual memory will be reduced due to a number of factors and may vary. Operating system also occupies some memory.

 2. The actual specs of products launched to the market shall take precedence over the info listed in this catalogue; any change may be made without prior notification.